



# Linealuce 27 Full Remote Configurator

## Project details & bill of quantities

Project date: 09 October 2025

[View this project online](#)

[Download CSV list](#)

VERIFY THIS PRODUCT LIST WITH AN IGUZZINI REPRESENTATIVE

The product list generated using this configurator is highly accurate but may contain imperfections due to the extremely high number of possible combinations. It is necessary to confirm the accuracy of this list with your iGuzzini representative before finalizing the order.

## Project details & bill of quantities

Code	Name	Q.ty
X781 	Constant voltage power supply unit non dimmable 80 W - Vin = 220-240 Vac 50/60Hz - Vout = 48 Vdc (43÷53 Vdc)	1
X188 	Wired DMX - 2-way junction connector - IP68	1
X773 	Cable with a female connector for IP68 monochrome LED With an anti-detachment locknut - L=350	1
X653 	Cable box IP66 - dim 378x188x130h	1
BZN7 	Y connector with 5 poles IP68 - For the connection of the DMX or DALI signal cable and power supply cable	1
9582 	Wired DMX - IP67 box for power supply - dim. 140x230x95h (6PG)	1
MWP3 	DALI-PWM interface LED dimmer 1-4 ch 12/24/48V 120/240W	1
UF42 	27 Surface Full Remote - Warm White - 48 Vdc - L=1511mm - Wide Flood optic - UF42	3
UE58 	27 Surface Full Remote - Warm White - 48 Vdc - L=625mm - Wide Flood optic - UE58	1

Set the driver at least at 47V.



When the power supply unit is installed at a distance of 10 m, to ensure the composition operates correctly, a cable with a cross-section of at least 1 mm<sup>2</sup> must be purchased separately. For the minimum cross-sectional area of the system power cable, follow the national regulations.

The bars listed may not completely cover the lengths indicated in the design.