

01010

Linealuce 27 surface Full Remote Configurator Project details & bill of quantities

Project date: 09 October 2025

View this project online

Download CSV list

Project details & bill of quantities

Code	Name	Q.ty
X781 🖸	Constant voltage power supply unit non dimmable 80 W - $Vin = 220-240 Vac 50/60 Hz$ - $Vout = 48 Vdc (43 \div 53 Vdc)$	1
X773 🖸	Cable with a female connector for IP68 monochrome LED With an anti-detachment locknut - L=350	1
X653 🖸	Cable box IP66 - dim 378x188x130h	1
BZN7 🖸	Y connector with 5 poles IP68 - For the connection of the DMX or DALI signal cable and power supply cable	1
9582 🖸	Wired DMX - IP67 box for power supply - dim. 140x230x95h (6PG)	1
MWP3 🖸	DALI-PWM interface LED dimmer 1-4 ch 12/24/48V 120/240W	1
UF42 🖸	27 Surface Full Remote - Warm White - 48 Vdc - L=1511mm - Wide Flood optic - UF42	3
UE58 🔼	27 Surface Full Remote - Warm White - 48 Vdc - L=625mm - Wide Flood optic - UE58	1

Set the driver at least at 47V.



When the power supply unit is installed at a distance of 10 m, to ensure the composition operates correctly, a cable with a cross-section of at least 1 mm² must be purchased separately. For the minimum cross-sectional area of the system power cable, follow the national regulations.

The bars listed may not completely cover the lengths indicated in the design.