



Linealuce 27 surface Full Remote Configurator

Project details & bill of quantities

Project date: 09 October 2025

[View this project online](#)

[Download CSV list](#)

VERIFY THIS PRODUCT LIST WITH AN IGUZZINI REPRESENTATIVE

The product list generated using this configurator is highly accurate but may contain imperfections due to the extremely high number of possible combinations. It is necessary to confirm the accuracy of this list with your iGuzzini representative before finalizing the order.

Project details & bill of quantities

Code	Name	Q.ty
X404 	Constant voltage power supply unit non dimmable 240W - VIN = 90-305VAC 47/63Hz Vout = 48Vdc (44,8÷51,2Vdc)	1
X170 	Cable with a female connector for IP68 monochrome LED With an anti-detachment locknut - L=3000	1
X653 	Cable box IP66 - dim 378x188x130h	1
BZN7 	Y connector with 5 poles IP68 - For the connection of the DMX or DALI signal cable and power supply cable	1
9582 	Wired DMX - IP67 box for power supply - dim. 140x230x95h (6PG)	1
9639 	DMX/DALI-PWM interface LED dimmer - 1-4ch 12/24/48V 720W max	1
UF40 	27 Surface Full Remote - Warm White - 48 Vdc - L=1511mm - Wall Grazing Wide Flood optic - UF40	6
UF12 	27 Surface Full Remote - Warm White - 48 Vdc - L=1216mm - Wall Grazing Wide Flood optic - UF12	1



Set the driver at least at 50V.

The bars listed may not completely cover the lengths indicated in the design.